



#### **Technical Parameters**

	Model	SM-2000L
Primary Lens	Optics	Achromatic opticalsystem
	Lens	OLYMPUS <sup>®</sup>
	Eyepieces	10X / 12.5X Wide-Angle Lens (Can Choose)
	Binoculars	30°Fixed Binoculars, 0°~180°Foldable (Can Choose)
	Pupil Distance	55~75mm
	Diopter	+5D~-8D
	Zoom System	4X~20X Continuous Zoom( Electric )
	Operating Distance	200mm
	Focus	40mm
	Inclination	0~30°
Assistant Lens	Modality	Zoom、Focus, Stereoscopic Same Light Path
	Magnification	4X、7X
	Position	Interchange (Left or Right)
X-Y Translation	Movement Range	50mm×50mm
	Reset	Auto-Reset
	Speed	2.2mm / sec
Illuminating	Modality	Aspherical Design
System	Illuminant	Twolamp15V / 150Whalogen Lamp (Imports)
	Control Mode	Continuou Dimming、Panel Control
	Illumination	≥70,000Lux
	Filter Light	Macular Protection、Green Filter、Cobalt Blue (Can Choose)
	Red Reflex	Adjustable
Machine Case	Arm Extension Length	1250mm
	Up and Down Adjust	±260mm
	Base Size	560mm×560mm
Multifunctional	X-Y Fine-Tuning, Electronic Focus, Electronic Zoom,	
Foot Switch	Light Adjustment, Light Switch	
Other	HD Video System、4K Video System、3D Stereo Image System	
Accessories	BIOM System\Invertor\Laser Protective Goggles	

Forte Biyoteknoloji San. Ve Tic. Ltd. Şti. www.fortebiyoteknoloji.com

Adalet Mah. Manas Bul. Folkart Towers A Kule 47/B K:26 D:2601 Bayraklı Izmir /

Türkiye

Tel: +90.232.332.04.82 Fax: +90.232.332.04.90

Email: info@fortebiyoteknoloji.com









A Stereo & Colorful View from Olympus Optics and Cormfort View Eye Pieces.


# **Key Feature**

**OLYMPUS** Higher resolution Excellent depth of view





### Aspherical condenser system



Red Reflex Clarity
Bright surgical view

#### **Multifunctional Foot Switch**





#### **Optics**



## **Video System**

Optional video clarity







2D&3D Video Solutions Optional photo and video interface upgraded to full configuration with imaging unit.